



SafeLite



SafeLite 20m



SafeLite 30m



Recessed Base



Cone diffuser



Plexi plate diffuser



SafeLite

Function	Use either as an emergency luminaire or exit sign
Testing system	Stand Alone
Housing	Polycarbonate, Glow wire test : 850°C, RAL9003
Type of mounting	Surface Options : Recessed base for ceiling, double sided cone diffuser, plexi plate diffuser, set of 3 exit legends (L, R, D)
Terminals	up to 1x2,5 mm ² per connection
Degree of protection	IK04, IP42 or IP65
Operation Mode	Non Maintained or Maintained & Non Maintained mode selectable
Connection voltage	230V +/- 5% [220V-240V] 50-60Hz
Permissible ambient temperature	+5°C to +40°C
Battery	Ni-Cd
Light source	LED strip
Duration	3 hours
Viewing distance	20m or 30m
Insulation class	II
Dimensions in mm	20 m viewing distance version: 270 x 119 x 49 30 m viewing distance version: 371 x 170 x 62

Order codes

Order code	Description	Viewing distance	Operation	IP	Lum in emergency	Lum in mains	IK	Duration	Battery	Weight (kg)
SL2-42D3D-CGL-C	SL20,MNM,IP42,100lm,3H	20m	MNM	42	100	100	04	3h	3.6V 1.7Ah	0.7
SL2-65D3D-CGL-C	SL30,MNM,IP42,200lm,3H	20m	MNM	65	100	100	07	3h	3.6V 1.7Ah	0.7

Accessories

SL23A	20m adhesive pictograms (L,R,D)
SL33A	30m adhesive pictograms (L,R,D)
SL23I	20m 3x Foils to insert inside the luminaire (L, R, D)
SL33I	30m 3x Foils to insert inside the luminaire (L, R, D)
SL3PPD	30m Plexi Plate 1 side down
SL3PPDD	30m Plexi Plate 2 sides down
SL3PPLR	30m Plexi Plate 2 sides L,R
SL2PPD	20m Plexi Plate 1 side down
SL2PPDD	20m Plexi Plate 2 sides down
SL2PPLR	20m Plexi Plate 2 sides L,R
SL2CD	SL20,Cone Diffuser*
SL3CD	SL30, Cone Diffuser*
SL2RB	SL20,Recessed Base, Plastic, RAL9003
SL3RB	SL30,Recessed Base, Plastic, RAL9003

*Pictograms have to be ordered separately