

WIRELESS CONVENTIONAL DETECTORS & ANCILLARIES



Ei605 Series



Ei603 Series



Ei413



Ei407

Our Ei range of RadioLINK wireless conventional detectors are BSI kitemarked / VDS approved to BS EN14604:2005.

All devices have built-in circuitry to aid suppression of voltage transients and RF interference (devices operate at RF frequency 868,499MHz).

Wireless zones - why?

- Eliminates expensive cable for detectors and sounders
- Difficult or impossible to run cable
- Hard to reach voids
- Listed and protected buildings
- Renovations and refurbishments
- Integrated detectors and sounders
- Up to 12 x RF alarms and 8 x ancillaries (e.g. MCP) per zone
- Multi-repeater and multi-path robust connectivity

RadioLINK Wireless Professional Battery Powered Smoke Alarms (Ei605 Series)

- Smoke Alarm - Optical Sensor
- RadioLINK interconnect & remote control
- Loud Alarm - 85dB (A) at 3 metres
- Large Test & Hush Button
- Easy Installation with twist-on base
- Model Ei605WRF - Replaceable Battery
- Model Ei605TYWRF - 10 Year Lithium Battery
- Certified to VdS EN 14604:2005
- 5 Year Guarantee

RadioLINK Wireless Professional Battery Powered Heat Alarms (Ei603 Series)

- Heat Alarm - Type A1 Sensor
- RadioLINK interconnect & remote control
- Loud Alarm - 85dB (A) at 3 metres
- Large Test Button
- Easy Installation with twist-on base
- Model Ei603CRF - Replaceable Battery
- Model Ei603TYCRF - 10 Year Lithium Battery
- Certified to BS 5446-2:2003
- 5 Year Guarantee

RadioLINK Wireless Interface Module to conventional fire panel (Ei413)

- RadioLINK Interface Module to conventional fire panels
- Signals to panel
 - Fire Alarm
 - Low battery fault
 - Smoke chamber fault
- 10 - 30V power from panel
- Works with Ei Electronics 600 Series RadioLINK Alarms & Accessories
- Contact input from panel to sound all alarms in zone
- 1 x Ei413 required for each Wireless Zone
- 5 Year Guarantee

RadioLINK Wireless Manual Call Point (Ei407)

- Wall mounted Manual Call Point
- Fully resettable
- Powered by 10 Year Battery
- Triggers all wireless alarms in the selected zone
- Triggers the Ei413 interface module to alert panel
- 5 Year Guarantee